

MERCHANT BAR REFERENCE GUIDE: UNEQUAL ANGLES



Designation	Weight	Surface Area	Side A b ₁	Side B b ₂	Thickness of Flange t _r
	kg/m	m²/m	mm	mm	mm
100x75x10	12.4	0.342	100	75	9.5
100x75x6	10.3	0.342	100	75	7.8
100x75x5	7.98	0.342	100	75	6.0
75x50x8	7.23	0.242	75	50	7.8
75x50x6	5.66	0.242	75	50	6.0
75x50x5	4.40	0.242	75	50	4.6
65x50x8	6.59	0.225	65	50	7.8
65x50x6	5.16	0.225	65	50	6.0
65x50x5	4.02	0.225	65	50	4.6





- Manufactured in accordance with the requirements of Australian Standard AS/NZS 3679.1 2016 in Grade 300.
- Grade 350 & 350L0 available on request.
- Non-standard lengths or cut to size on request.



Pg

17

522 Cross Keys Road Cavan SA 5094

+61 8 8405 7111

sdsales@brice.com.au www.brice.com.au

Please note: Whilst all care has been taken, no responsibility can be accepted for any errors. Weights supplied and charged will vary in accordance with standard mill tolerance and practice. February 2024 Revision 5